

## Intellia Hydrogen Sulfide (H<sub>2</sub>S) Gas Detector INT-Gas-04

### Serviceable Single-gas Detector

The next-generation single-gas detector that helps you reduce cost, ensure compliance and know your workers are protected. Intellia Hydrogen Sulfide (H<sub>2</sub>S) has everything you expect — plus additional features to make your compliance easier and more cost-effective than ever. All with a reliable life span, one-button operation and small, lightweight profile. Intellia Hydrogen Sulfide (H<sub>2</sub>S) has:

- The easiest single-gas detector to service, with no need to take it apart to replace sensors, batteries and sensor filters. That means long life and low cost.
- Complete with an extensive selection of sensor options. Count on comprehensive detection, whether you're monitoring for common or exotic hazards.
- The first single-gas detector with the 1-Series sensor for CO, H<sub>2</sub>S and O<sub>2</sub>. That means high accuracy, lower costs and faster sensor response time for the gases you monitor most often.
- Compatible with IntelliDoX. Save time and centralize data with automated bump testing, calibration and instrument management.



H <sub>2</sub> S	CO	O <sub>2</sub>
NH <sub>3</sub>	SO <sub>2</sub>	HCN
Cl <sub>2</sub>	NO	NO <sub>2</sub>
PH <sub>3</sub>	ETO	ClO <sub>2</sub>
O <sub>3</sub>	H <sub>2</sub>	



Easy to handle



Easy to read



Easy to service



Easy to see

## FEATURES & BENEFITS

**For even more time-saving convenience — plus remote visibility on alarms — choose the wireless version. And manage it from your smartphone.**

Pair the wireless Intellia Hydrogen Sulfide (H<sub>2</sub>S) detector with our Safety Communicator mobile app and detector readings are sent instantly to Intellia real-time monitoring software. Access it from any device with an internet connection, and get remote visibility on worker safety and location.

You can also use the wireless Intellia Hydrogen (H<sub>2</sub>S) detector to share gas data with the desktop software — no dock required.

### Other Intellia Hydrogen Sulfide (H<sub>2</sub>S) features:

- Option to activate IntelliFlash™ or non-compliance flash
- Ability to assign detectors to workers and locations
- Easy-to-read display for multiple languages
- Data logging with rolling 24-hour peak reading

# Intellia Hydrogen Sulfide (H<sub>2</sub>S) Gas Detector Technical Specifications

TECHNICAL SPECIFICATIONS	
SIZE	2.7 x 2.6 x 1.4 in. / 7.0 x 6.7 x 3.6 cm (1-Series sensor models) 2.7 x 2.6 x 1.6 in. / 7.0 x 6.7 x 4.1 cm (4-Series sensor models)
WEIGHT	3.6 to 4.1 oz. / 103 to 116 g, depending on installed sensor
HUMIDITY	0% - 95% RH (non-condensing)
INGRESS PROTECTION	IP66/68
ALARMS AND TYPE	Visual, vibrating, audible (95 dB); Low, High, TWA, STEL, non-compliance
SELF-TEST	Sensor integrity, circuitry, battery and audible/visual alarms on activation; battery (continuous)
TYPICAL BATTERY LIFE	12 months (6 months for 1-Series O <sub>2</sub> )
CONNECTED WORKER	<ul style="list-style-type: none"> <li>Bluetooth™ Low Energy (BLE)</li> </ul>
USER OPTIONS	<ul style="list-style-type: none"> <li>Reset TWA, STEL and Peak readings</li> <li>Change High, Low, TWA and STEL alarm setpoints</li> <li>Latching alarms</li> <li>Enable IntelliFlash and non-compliance indicators</li> <li>Set calibration and/or bump test reminders</li> <li>Assign worker and location assignments</li> <li>Language select: English, French, Spanish, German, Italian, Russian, Japanese, Chinese, Korean, Portuguese, Dutch (<i>English, Russian, Japanese, Chinese and Korean only</i>)</li> </ul>
CERTIFICATIONS AND APPROVALS	<p><b>CE</b>: Class I, Division 1, Groups A, B, C, D T4 Class I, Zone 0, AEx/Ex ia IIC T4 Ga -40°C ≤ Tamb ≤ 60°C</p> <p><b>ATEX</b>: Sira 18ATEX2243 <b>CE</b> 2460 <b>Ex</b> II 1G Ex ia IIC T4 Ga <b>Ex</b> I M1 Ex ia I Ma -40°C ≤ Tamb ≤ 60°C</p> <p><b>IECEX</b>: IECEX SIR 18.0058 Ex ia IIC T4 Ga / Ex ia I Ma -40°C ≤ Tamb ≤ 60°C</p> <p><b>FCC ID</b>: SU3BWS1</p> <p><b>IC</b>: 20969-BWS1</p> <p><b>RED</b>: RE-D Directive 2014/53/EU</p> <p>For additional certifications, please review the manual or consult <b>Intellia Analytics</b>.</p>
WARRANTY	3 years for 1-Series detectors and sensors (H <sub>2</sub> S, CO, O <sub>2</sub> ) 2 years for 4-Series detectors and sensors (1 year for NH <sub>3</sub> , Cl <sub>2</sub> , O <sub>3</sub> , ETO, ClO <sub>2</sub> sensors)

SENSOR SPECIFICATIONS			
GASES	STANDARD MEASURING RANGE	RESOLUTION	OPERATING TEMPERATURE
H <sub>2</sub> S (1S)	0-200 ppm	0.1 ppm	-40 to +140°F / -40 to +60°C
CO (1S)	0-2000 ppm	1 ppm	-40 to +140°F / -40 to +60°C
O <sub>2</sub> (1S)	0-30% v/v	0.1% v/v	-40 to +140°F / -40 to +60°C
CL <sub>2</sub> (4S)	0-50 ppm	0.1 ppm	-4 to +104°F / -20 to +40°
CLO <sub>2</sub> (4S)	0-1 ppm	0.01 ppm	-4 to +104°F / -20 to +40°
CO-H (4S)	0-2000 ppm	0.5 ppm	-22 to +122°F / -30 to +50°C
ETO (4S)	0-100 ppm	0.1 ppm	-22 to +122°F / -30 to +50°C
H <sub>2</sub> (4S)	0-1000 ppm	2 ppm	-4 to +122°F / -20 to +50°
H <sub>2</sub> S (EXT. RANGE) (4S)	0-500 ppm	0.1 ppm	-40 to +122°F / -40 to +50°C
HCN (4S)	0-100 ppm	0.1 ppm	-22 to +122°F / -30 to +50°C
NH <sub>3</sub> (4S)	0-100 ppm	1 ppm	-4 to +104°F / -20 to +40°
NH <sub>3</sub> (EXT. RANGE) (4S)	0-1000 ppm	1 ppm	-4 to +104°F / -20 to +40°
NO (4S)	0-250 ppm	0.2 ppm	-22 to +122°F / -30 to +50°C
NO <sub>2</sub> (4S)	0-100 ppm	0.1 ppm	-4 to +122°F / -20 to +50°
O <sub>3</sub> (4S)	0-1 ppm	0.01 ppm	-22 to +122°F / -30 to +50°C
PH <sub>3</sub> (4S)	0-5 ppm	0.1 ppm	-4 to +122°F / -20 to +50°
SO <sub>2</sub> (4S)	0-100 ppm	0.1 ppm	-22 to +122°F / -30 to +50°C
H <sub>2</sub> S (4S)*	0-100 ppm	0.1 ppm	-40 to +140°F / -20 to +50°C
CO (4S)*	0-1000 ppm	1 ppm	-40 to +140°F / -20 to +50°C
O <sub>2</sub> (4S)*	0-30% v/v	0.1% v/v	-40 to +140°F / -20 to +50°C

1S = 1-Series sensor / 4S = 4-Series sensor

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



## INTELLIDOX DOCKING SYSTEM

*IntelliDoX combines smart-docking modules with our instrument management system to provide automated testing and record keeping.*