

## Intellia Hydrogen Sulfide (H<sub>2</sub>S) Gas Detector INT-Gas-04

### Serviceable Single-gas Detector

The next-generation single-gas detector that helps you reduce cost, ensure compliance and know your workers are protected. Intellia Hydrogen Sulfide (H<sub>2</sub>S) has everything you expect – plus additional features to make your compliance easier and more cost-effective than ever. All with a reliable life span, one-button operation and small, lightweight profile. Intellia Hydrogen Sulfide (H<sub>2</sub>S) has:

- The easiest single-gas detector to service, with no need to take it apart to replace sensors, batteries and sensor filters. That means long life and low cost.
- Complete with an extensive selection of sensor options. Count on comprehensive detection, whether you're monitoring for common or exotic hazards.
- The first single-gas detector with the 1-Series sensor for CO, H<sub>2</sub>S and O<sub>2</sub>. That means high accuracy, lower costs and faster sensor response time for the gases you monitor most often.
- Compatible with IntelliDoX. Save time and centralize data with automated bump testing, calibration and instrument management. Use IntelliDoX docking stations with Honeywell SafetySuite Device Configurator software.



Easy to handle



Easy to read



Easy to service



Easy to see

H <sub>2</sub> S	CO	O <sub>2</sub>
NH <sub>3</sub>	SO <sub>2</sub>	HCN
Cl <sub>2</sub>	NO	NO <sub>2</sub>
PH <sub>3</sub>	ETO	ClO <sub>2</sub>
O <sub>3</sub>	H <sub>2</sub>	

## FEATURES & BENEFITS

**For even more time-saving convenience – plus remote visibility on alarms – choose the wireless version. And manage it from your smartphone.**

Pair the wireless Intellia Hydrogen Sulfide (H<sub>2</sub>S) detector with our Safety Communicator mobile app and detector readings are sent instantly to Intellia real-time monitoring software. Access it from any device with an internet connection, and get remote visibility on worker safety and location.

You can also use the wireless Intellia Hydrogen (H<sub>2</sub>S) detector to share gas data with the desktop software – no dock required.

**Other Intellia Hydrogen Sulfide (H<sub>2</sub>S) features:**

- Option to activate IntelliFlash™ or non-compliance flash
- Ability to assign detectors to workers and locations
- Easy-to-read display for multiple languages
- Data logging with rolling 24-hour peak reading

# Intellia Hydrogen Sulfide (H<sub>2</sub>S) Gas Detector Technical Specifications

TECHNICAL SPECIFICATIONS	
<b>SIZE</b>	2.7 x 2.6 x 1.4 in. / 7.0 x 6.7 x 3.6 cm (1-Series sensor models) 2.7 x 2.6 x 1.6 in. / 7.0 x 6.7 x 4.1 cm (4-Series sensor models)
<b>WEIGHT</b>	3.6 to 4.1 oz. / 103 to 116 g, depending on installed sensor
<b>HUMIDITY</b>	0% - 95% RH (non-condensing)
<b>INGRESS PROTECTION</b>	IP66/68
<b>ALARMS AND TYPE</b>	Visual, vibrating, audible (95 dB); Low, High, TWA, STEL, non-compliance
<b>SELF-TEST</b>	Sensor integrity, circuitry, battery and audible/visual alarms on activation; battery (continuous)
<b>TYPICAL BATTERY LIFE</b>	12 months (6 months for 1-Series O <sub>2</sub> )
<b>CONNECTED WORKER</b>	<ul style="list-style-type: none"> <li>Bluetooth™ Low Energy (BLE) – Ability to connect to Honeywell's Safety Communicator App</li> </ul>
<b>USER OPTIONS</b>	<ul style="list-style-type: none"> <li>Reset TWA, STEL and Peak readings</li> <li>Change High, Low, TWA and STEL alarm setpoints</li> <li>Latching alarms</li> <li>Enable IntelliFlash and non-compliance indicators</li> <li>Set calibration and/or bump test reminders</li> <li>Assign worker and location assignments</li> <li>Language select: English, French, Spanish, German, Italian, Russian, Japanese, Chinese, Korean, Portuguese, Dutch (<i>Honeywell BW™ Solo Lite*: English, Russian, Japanese, Chinese and Korean only</i>)</li> </ul>
<b>CERTIFICATIONS AND APPROVALS</b>	<p><b>CE</b>: Class I, Division 1, Groups A, B, C, D T4 Class I, Zone 0, AEx/Ex ia IIC T4 Ga -40°C ≤ Tamb ≤ 60°C</p> <p><b>ATEX</b>: Sira 18ATEX2243 CE 2460 Ex II 1G Ex ia IIC T4 Ga Ex I M1 Ex ia I Ma -40°C ≤ Tamb ≤ 60°C</p> <p><b>IECEX</b>: IECEX SIR 18.0058 Ex ia IIC T4 Ga / Ex ia I Ma -40°C ≤ Tamb ≤ 60°C</p> <p><b>FCC ID</b>: SU3BWS1</p> <p><b>IC</b>: 20969-BWS1</p> <p><b>RED</b>: RE-D Directive 2014/53/EU</p> <p>For additional certifications, please review the manual or consult <b>Intellia Analytics</b>.</p>
<b>WARRANTY</b>	3 years for 1-Series detectors and sensors (H <sub>2</sub> S, CO, O <sub>2</sub> ) 2 years for 4-Series detectors and sensors (1 year for NH <sub>3</sub> , Cl <sub>2</sub> , O <sub>3</sub> , ETO, ClO <sub>2</sub> sensors)

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



## INTELLIDOX DOCKING SYSTEM

*IntelliDoX combines smart-docking modules with our instrument management system to provide automated testing and record keeping.*

SENSOR SPECIFICATIONS			
GASES	STANDARD MEASURING RANGE	RESOLUTION	OPERATING TEMPERATURE
H <sub>2</sub> S (1S)	0-200 ppm	0.1 ppm	-40 to +140°F / -40 to +60°C
CO (1S)	0-2000 ppm	1 ppm	-40 to +140°F / -40 to +60°C
O <sub>2</sub> (1S)	0-30% v/v	0.1% v/v	-40 to +140°F / -40 to +60°C
Cl <sub>2</sub> (4S)	0-50 ppm	0.1 ppm	-4 to +104°F / -20 to +40°
ClO <sub>2</sub> (4S)	0-1 ppm	0.01 ppm	-4 to +104°F / -20 to +40°
CO-H (4S)	0-2000 ppm	0.5 ppm	-22 to +122°F / -30 to +50°C
ETO (4S)	0-100 ppm	0.1 ppm	-22 to +122°F / -30 to +50°C
H <sub>2</sub> (4S)	0-1000 ppm	2 ppm	-4 to +122°F / -20 to +50°
H <sub>2</sub> S (EXT. RANGE) (4S)	0-500 ppm	0.1 ppm	-40 to +122°F / -40 to +50°C
HCN (4S)	0-100 ppm	0.1 ppm	-22 to +122°F / -30 to +50°C
NH <sub>3</sub> (4S)	0-100 ppm	1 ppm	-4 to +104°F / -20 to +40°
NH <sub>3</sub> (EXT. RANGE) (4S)	0-1000 ppm	1 ppm	-4 to +104°F / -20 to +40°
NO (4S)	0-250 ppm	0.2 ppm	-22 to +122°F / -30 to +50°C
NO <sub>2</sub> (4S)	0-100 ppm	0.1 ppm	-4 to +122°F / -20 to +50°
O <sub>3</sub> (4S)	0-1 ppm	0.01 ppm	-22 to +122°F / -30 to +50°C
PH <sub>3</sub> (4S)	0-5 ppm	0.1 ppm	-4 to +122°F / -20 to +50°
SO <sub>2</sub> (4S)	0-100 ppm	0.1 ppm	-22 to +122°F / -30 to +50°C
H <sub>2</sub> S (4S)*	0-100 ppm	0.1 ppm	-40 to +140°F / -20 to +50°C
CO (4S)*	0-1000 ppm	1 ppm	-40 to +140°F / -20 to +50°C
O <sub>2</sub> (4S)*	0-30% v/v	0.1% v/v	-40 to +140°F / -20 to +50°C

1S = 1-Series sensor / 4S = 4-Series sensor